

## DELK 130/20 PP

The stable and effective hanging spherical DELK 130/20 PP1 loudspeakers are made of high quality powder coated steel that is completely corrosion-resistant. They are equipped with a high quality broadband speaker with a diameter of 130 mm. Aesthetic and unique housing offers exceptional quality of the sound. Because of suspended mounting system, the speakers DELK 130/20 PP1 can be placed in places inaccessible to the installation of other speakers. The sets are equipped with an installation box in which there is a 3-pin ceramic cube

together with an overload fuse connected to the loudspeaker by the HTKSH-PH90 cable additionally secured with a steel cable of adjustable length. The loudspeaker is equipped with a thermal fuse installed directly under the dome of the loudspeaker. The set is used in systems with line continuity monitoring by impedance method. Additionally, when installing as a cover element, the OsKs cable cover in a color similar to the speaker's color is used. The standard length of the HTKSH wire is 2 m.



Technical data	
Symbol	DELK 130/20 PP1
Nominal power	20W
Speaker type	130 mm wideband
Frequency range (-10dB)	205 – 20 100 Hz
SPL 1W/1m	96,4 dB
SPL Pmax/1m	109,4 dB
Emission angle 1.000 Hz (-10 dB)	150°
Transformer type	100V, 20/15/10/5 W
Dimensions	180 mm
Weight	2,8 kg
Material	Steel, powder coated
Connector	3-pin ceramic cube
Colour	RAL-9010 White/whole RAL palette
VPE	8

