





WAL 165/10 PP WAL 165/10 PP1

WAL 165/10 PP - these elegant, rectangular, compact wall loudspeakers are made of high-grade MDF, and the cabinets are finished in white or optionally black color. Due to their shape, material, and fitting way, they are suitable for a wide range of applications as hotels, dormitories, commercial buildings, hospitals, schools, etc. They are equipped with a high quality 10 W 165 mm full-range speaker and 100 V transformer. The connection unit has ceramic terminal block with thermal fuse. The loudspeaker has IP 54 rating. It is optionally offered in PP1 version – it means instead of ceramic block and thermal fuse it is equipped just with a plastic connection block.



Model	WAL 165/10 PP WAL 165/10 PP1
Type	wall box
Application	on wall
Certificate Number	1438-CPR-0700
Speaker Type	165 mm full-range
Rated power [W]	10
Driver impedance [Ω]	8
Impedance 100V [Ω]	1000/1666/3333/6666
Tappings 100V [W]	10/6/3/1,5
Frequency Range (-10dB) [Hz]	145-20 000*
SPL 1W/1 m [dB]	99,2*
SPL Pmax/1 m [dB]	109,2*
Sensitivity 1W/4 m EN 54-24 [dB]	78,1
Sensitivity rated power/4 m EN 54-24	89,2
Dispersion -6dB, 500 Hz/1 kHz/2 kHz/4kHz [°]	H: 180/100/100/75; V: 180/90/87,5/72,5
Connection PP/PP1	2x3 pole ceramic cube/ 2x2 pole conector
Temperature range [°C]	<-10, +55>
Type A/B/C	A
IP Rating according to EN 54-24 / IP Rating	21C/54*
Dimensions [mm]	253 x 193 x 83
Weight [kg]	1,9
Material	MDF
Colour	RAL 9010
Packing Unit	8

* measured in institute other than BIP CNBOP

