

ZDSOP24 – IVO SYSTEM POWER SUPPLY



Certificate of constancy of performance 1438-CPR-1077
Certificate of admittance 5641/2025

EN54 16

FEATURES

- High efficiency: up to 90 %
- High-power rated output up to 3460 W
- Compact size
- Direct 24 V DC output
- Modbus communication
- Maximum battery capacity: 2 × 230 Ah
- Over voltage, over current, short circuit and temperature protection

OVERVIEW

The ZDSOP24 power supply unit is designed to provide uninterrupted and stabilized 24 V DC power to IVO system components. It supports a modular configuration with power supply modules ranging from 500 W up to 3460 W.

The unit features independently protected outputs for up to eight amplifiers, one system controller (bridgeable with KG-ETH, KAS, and 16SG modules), and one auxiliary device. Housed in a standard 19" rack-mount enclosure, the ZDSOP24 operates from a 230 V AC mains supply via a single-phase, three-wire connection (phase, neutral, ground). In case of mains power failure, the system automatically switches to a 24 V DC battery backup, ensuring continuous operation of all connected devices.

The ZDSOP24 supports maintenance-free Sealed Lead-Acid (SLA) batteries, including both AGM and gel types. Depending on the version, it can accommodate one or two battery strings, each with a capacity of up to 230 Ah, providing a maximum backup capacity of 460 Ah.

An advanced battery resistance monitoring function enables independent supervision of each battery string, ensuring optimal performance and compliance with both regulatory and project-specific requirements.

TECHNICAL SPECIFICATION

GENERAL

Power supply	230 V AC -15 % / +10 %
Total efficiency	> 87 %
Idle consumption	< 6 W
Standards	EN54, EN12101, CE
Operating temperature	-5 : +50 °C
Relative humidity	25 % - 90 %
Indicators	AC main, DC, fault, each output: DC status
Connectors	230 V AC, Outputs: 1x 24 V DC AUX, 1x 24 V DC controller, 8x 24 V DC amplifiers, EPS fault (230 V AC loss), PSU general fault, temperature sensor, RS485

OTHERS

Output voltage	20 - 29 V DC
----------------	--------------

BATTERY

Max. battery capacity	2x 230 Ah
-----------------------	-----------

SPECIFICATION PER VERSION RATED OUTPUT POWER BATTERY LINES MECHANICAL

ZDSOP24-05	500 W	1	1U, 19"
ZDSOP24-1-1	1000 W	1	1U, 19"
ZDSOP24-1-2	1000 W	2	1U, 19"
ZDSOP24-2-1	2000 W	1	1U, 19"
ZDSOP24-2-2	2000 W	2	1U, 19"
ZDSOP24-3-2	3000 W	2	2U, 19"
ZDSOP24-4-2	3460 W	2	2U, 19"

All rights reserved.

The information contained in this document is believed to be accurate; however, no representation or warranty is given, and pAudio Technologies assumes no liability regarding its accuracy or completeness.