

## 30 Watts IP Monitor / Wall mount Loudspeaker

### APPLICATION

- Public Address and Voice Alarm
- Outdoor application
- Background Music

### AREA OF USE

- Health • Education • Retail • Hospitality
- Stadiums • Transportation • Theme parks • Military



- powerful sound
- IEEE 802.3at/PoE plus high-
- impact ABS housing

### OVERVIEW

With our new Dante speakers, you can easily and cost-effectively implement audio-over-IP installations. The WMSIP-30W Dante monitor speaker is an active 2-way bass reflex speaker with exceptional acoustic properties.

With a 30W power output and a highly efficient Class D amplifier, it delivers powerful crystal-clear sound that will impress even the most demanding listeners. The 6.5" woofer and 1" tweeter ensure impressive sound fidelity across the entire frequency range of 77 to 21.500 Hz, reaching a maximum sound pressure level of 104,8 .

Thanks to the IEEE 802.3at/PoE plus RJ45 connector, the speaker can be easily integrated into existing networks. In addition to the power supply via PoE, a local 24V DC input is also possible, offering installation flexibility. The impact-resistant ABS housing offers robustness for demanding environments.

A wall bracket is included in the delivery, which makes installation particularly easy.

Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11 are required to use the Dante system.

## TECHNICAL DATA (ELECTRICAL)

Description	WMSIP-30W
Power	30W
Frequency Range	45 - 21.000 Hz
Frequency Response	70 - 20.000 Hz

## TECHNICAL DATA (MECHANICAL)

IP Rating	IP21
Weight (net)	3,9 kg
Temperature Range	-10 / +55 C°
Mounting	Swivel bracket
Connector	RJ45
Colour	white

### All rights reserved.

The information contained in this document is believed to be accurate; however, no representation or warranty is given, and pAudio Technologies assumes no liability regarding its accuracy or completeness.